




## FSN-TPD



- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: Fine thread
- Screw head: Trumpet shape head
- Suitability: Thick metal profiles up to 0,7 mm without pre-drilling




Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton		GTIN (EAN Code)
d [mm]	l [mm]	l <sub>g</sub> [mm]	d <sub>k</sub> [mm]			[pcs]	[pcs]		
<b>3.5</b>	25	19	8.3	PH 2	<b>040512</b>	1.000	8.000		40 0620 9405 123
	35	29	8.3	PH 2	<b>665001</b>	1.000	4.000		40 4896 2052 039
	45	39	8.3	PH 2	<b>665002</b>	1.000	4.000		40 4896 2052 046
	55	49	8.3	PH 2	<b>665003</b>	1.000	4.000		40 4896 2052 053
<b>3.9</b>	25	19	8.3	PH 2	<b>665007</b>	1.000	8.000		40 4896 2052 091
	30	24	8.3	PH 2	<b>665011</b>	1.000	6.000		40 4896 2052 138
	35	29	8.3	PH 2	<b>665015</b>	1.000	4.000		40 4896 2052 176
	45	39	8.3	PH 2	<b>665019</b>	1.000	4.000		40 4896 2052 213
	55	49	8.3	PH 2	<b>665022</b>	600	2.400		40 4896 2052 244

## FSN-TPDM

- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: Fine thread
- Screw head: Trumpet shape head
- Suitability: Thick metal profiles up to 0,7 mm without pre-drilling
- Specially: collated, belt system for strip screws



Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton		GTIN (EAN Code)
d [mm]	l [mm]	l <sub>g</sub> [mm]	d <sub>k</sub> [mm]			[pcs]	[pcs]		
<b>3.5</b>	25	19	8.3	PH 2	<b>040603</b>	1.000	4.000		40 0620 9406 038
	35	29	8.3	PH 2	<b>665088</b>	1.000	4.000		40 4896 2052 909
	45	39	8.3	PH 2	<b>665089</b>	1.000	4.000		40 4896 2052 916