





Renovate with Smartpanel Wetwall.

These high-quality waterproof panels are available in a wide range of finished designs regarding colors, structures, and tile patterns, which makes it simple to create just the style you desire in your bathroom.

The joint width is 2mm and the sealant colors vary between grey, white and black. The moldings are delivered in the same solors as the sealant your panels holds, colors, to ensure a perfect result.

click system

The panels are easily mounted with a click system that ensures a smooth transition between the panels. Standard length is 240 cm, but many of the designs are also available in 302 cm and we are pleased to cut them at a specific length to reduce your workload and waste. They are approved in accordance with SINTEF and the Wet Room Standard from the Norwegian BVN - a tool for planning and building wetrooms..

Sertified Antibacterial surface:

Our laminates are sertified according to JIS 2801-2012 and gives a min. of 95% protection.

With sustainable core structure

Huntonit Pro Wall + Smartpanel Wetwall

Huntonit products for internal walls and ceilings are natural products that does not emit any gas or odors when exposed to external influences (sun, heat, moisture, etc.). The boards are made in a wet process where the natural fibers are mixed with water, heated up and pressed together into boards. The process is done without the addition of glue, but uses the wood fibers' own binder, lignin.

The boards are then cut into panels and Smartpanel uses state of the art machines for installing membrane and laminate. Designs are implemented and the panels are ready for your local building materials retailer.

Huntonit interior products for ceilings and walls are the only painted interior panel recommended by the Norwegian Asthma and Allergy Association.

Huntonit ceiling products with 20-year guarantee

- also used in wet rooms
- and is recommended for use with Wetwall.







Smartpanel Wetwall Accessories:

COLLECTIONS	8
TILEPATTERNS	9
COLECTION COLOR SILK	11
COLLECTION COLOR HIGHGLOSS	13
COLLECTION WOOD	15
COLLECTION STONE/CEMENT	17
COLLECTION FANTASY	18
APPROVALS AND COLOR CODES	19

PROFILES	25
INSTALLATION INSTRUCTIONS SMARTPANEL WETWALL	26

Kitchen Board

COLLECTION KITCHEN BOARD 23





Smartpanel Wetwall

Good morning!







Extra hight on your project?






We do deliver Wetwall panels in both 2720mm and 3020mm length.


We cut all lengths from 3020mm and below - at your request - then you will avoid the job of cutting and we will contribute to less waste on the construction site. No additional cost.

Contact your contact person for information about decorations, delivery times and price.

Collections


We have selected 5 collections with beautiful surfaces and colours






Tilepattern

NJ - stands for Narrow Joint, which is a nice 2 mm narrow joint.










Collection Color Silk

The silky feeling
Solid colored bathroom panels with a silk surface. Easy to clean, gives a pleasant feeling, often preffered with a limited tile pattern.

Combine the decors and tile patterns you want.








Collection Color High Gloss

High-gloss bathroom walls give a sense of cleanliness. The light is reflected and it feels sparkling clean. Dimmable lighting is recommended so that a peaceful time can also be enjoyed.



HARMONY, WARMTH AND AND NATURE





Collection Wood

We the Nordic people, have a long history of love for our proximity to nature and the forest. This collection gives a slice of nature and the peace it brings. Enjoy your bath.

Wetwall panels can be combined - a combination of boards from Wood and solid color is lovely and personal. There is also no reason why these gorgeous walls should be limited to the bathroom.



9610 E Pure Ash w/White joint



5427 E Refresh Oak w/black joint



5758 E Artisan Oak w/grey joint



5331 E Midnight Acasia w/grey joint






S 5575 Black Marble silk w/grey joint



HG 5575 Black Marble HG w/black joint



S 5574 Stutario silk w/grey joint

Collection Stone / Cement

Industrial look in the interior is still a popular trend.

Choose between concrete, marble, stone or slate - and give your bathroom a lift.

Also suitable in other contexts - both commercial and private - think possibilities.

Wetwall panels can be combined. Please remember the lighting when planning bathroom.



VRB 5577 Houston w/grey joint



VRB 5578 Madison w/grey joint



Terra 5774 Antico w/grey joint



Terra 5773 Neptunite w/black joint

FANTASY



HG 9951 Bianca Dust w/white joint

HG 9960 Nero Dust w/black joint



Smartpanel AS is a company in Byggma Group. Product development with sustainability as a guiding principle is essential for all of us in the group.

Of the UN's 17 sustainability goals, we focus on 8. We have chosen our main focus where we believe we can contribute and where our influence can have the most positive effect.

































Color codes/ NCS S codes

The visual color is affected by lighting and reflection of light in relation to the surface. Therefore always check the product in addition to the NCS S code. The Smartpanel Wetwall boards are also affected by the joint color the boards have.

101 - Classic White	NCS S 0500 N
107 - White	NCS S 0502 Y
132 - Cyclone	NCS S 2502 Y50R
133 - Moonstone	NCS S 1505-Y40R
149 - Sheer	NCS S 2005-Y60R
163 - Bay	NCS S 3010-Y40R
166 - Blush Pink	NCS S 2020-Y80R
247 - Dutch Green	NCS S 1002-G30Y
201 - Maroon	NCS S 5040-R

261 - Dark Grey	NCS S 6502-B
266 - Ash Grey	NCS S 5000-N
271 - Light Grey	NCS S 1502-R50B
274 - Pine Nut	NCS S 6005-Y20R
275 - Pearl Grey	NCS S 1502-Y
401 - Black	NCS S 9000-N

19

SMARTPANER KITCHEN BOARD

PLEASURE &







SMARTENAL STATES

Smartpanel Kitchen Board gives your kitchen a boost in no time. The panels are installed to the wall between the bench and closet. Can be installed directly on existing wall or studwork.

They protect against spills, stains and heat, and are easy to clean. Smartpanel Kitchen comes in several different designs and can be easily combined for a unique look.











- 1. The classic white decor
- 2. Why not go for a dark Kitchen board with good lighting it gives a very pleasant atmosphere.



Tilepattern

NJ - Narrow Joint - is a discreet 2mm narrow joint. All Kitchen Boards have dimentions 11x620x580mm. (net sizes of KB: $11 \times 600 \times 580$ mm) They are delivered in packs of 2 - easy to handle.

NJ 00	NJ 01	N.J	NJ 60x30			
		_				
NJ 30x30	NJ 60x20	N.J	15x15			

NJ 06x58


Collection




An easy way to renew your kitchen and to take care of it.

Smartpanel Kitchen Board protects your wall between the worktops and upper cabinets. Makes it is easy to clean any food spills and water.


The decors are also available in full height so you can combine as you like.




K 101 Silk Classic White w/grey joint



K 107 Silk White w/grey joint



K 101 HG Classic White w/grey joint



K 107 HG White w/grey joint



K 5427 E Refresh Oak w/black joint



K 5575 Silk Black Marble w/grey joint



K 5574 Terra Antico w/grey joint



K 5577 VRB Houston w/grey joint

smartpanel WETWALL

CORRECT ACCESSORIES -EASY ASSEMBLY



















Block for easy essembly



Base profile Alu - White - Black




Edge profile Alu - White - Black

Accesories Profiles


Smartpanel WETWALL profiles are specially made for our products and an important element to achieve correct installation and 100% waterproof walls.

The profiles are delivered in alu, white and black.


As a service, all profiles are supplied with the necessary screws in a separate bag attached to the profile. Profiles are pre-drilled for screws.



External corner profile 2400 mm: Alu - White - Black



2-pcs Internal corner profile 2400mm: Alu - White - Black



Internal corner profile 2400mm: Alu - White - Black

Installation tips: Smartpanel WETWALL
If the boards are mounted on studs, extra care must be taken when fixing near differences in level/stepping. Be especially aware of power boxes etc. that are attached to the outside of studs.

smartpanel WETWALL

Base profile

1) Base profile trim is not a requirement in

dry zones, but we recommend the use of

base profile trims throughout the room.

The profile trim is fitted in line with the up-


per edge of the floor 60-80 mm. The mem-

brane must be applied 25 mm higher than


the upper edge. Behind the upper edge there must be sufficient screw fastening

to the profile trim. Installation must always


ALWAYS seal ALL cut surfaces on the panel with Smartpanel Wetwall SEAL.




For screw fastening to the rear wall, 18 mm Ergoboard/chip-board may be used



3) Make sure that the base profile trim is level before mounting. This is very important to achieve a good result.





4) Screw the base profile trim in place with the screws provided. Use the pre-drilled holes.




5) Seal the bottom edge of the base profile trim if you have tiles so that water doesn't remain on top of the tile.

Take extra care to ensure that there is sufficient sealant in corners.








6) Illustrations showing solutions for starting at a door or an inside corner. 6b is only used for 2-pcs internal corner profiles.


Correct installation accessories must be used for waterproof and correct installation.

Acclimatise in stabile room conditions for 3 days before installation.


When renovating or mounting on a wall with an existing vapour barrier, the vapour barrier must always be punctured or removed.




7) Screw part 1 of the internal corner profile in place. If the corner is not plumb, the panel must be adapted to the deviation. Cut the panel so that the rough edge is on the back of the panel. If the panel is too long, always cut the excess length from the top of the panel to accommodate the sill drip profile at the bottom, as well as to maintain the tile pattern.




8) Make sure the panel leveled before screwing it in at the top. Pre-drilling in the top of the panels is recommended. The panels must always be installed from left to right to ensure that they are placed drip edge down.




9) Adjust the panel so that it is in contact with the studs on the right. Make sure that the panel is plumb before installing it. Screw into the top of the panel and into the groove. Max. distance between the screws is 200 mm.




10) Click the next panel into place. Screw into the top of the panel and into the groove. Max. distance between the screws is 200 mm. The bottom screw must be 200 mm from the base profile trim



11) If the panels are to be installed in a wet zone, apply Smartpanel Wetwall SEAL sealant in the joint. The sealant must be applied in the upper edge of the groove (as shown in the illustration). All the panel's cut surfaces must always be sealed with Smartpanel Wetwall SEAL. See illustration 22 for wet zone description.



12) Apply enough Wetwall SEAL sealant to allow the sealant to seep out over the entire length of the joint.



13) Click the panels together. Spray on Wetwall CLEAN, remove excess sealant with Smartpanel Wetwall sealing tools. Wipe clean with Smartpanel Wetwall WIPES. Continue in the same way until you come to a pipe penetration or a corner.

Installation tips: Smartpanel WETWALL


Ideal substrates for mounting Smartpanel Wetwall are Ergoboard, chipboard, OSB etc.

If the boards are mounted on studs, extra care must be taken when mounting the boards near differences in I evel/stepping in the substrate. Power boxes and the like that are attached to the outside of poles must be embedded.




Pipe penetration


14) Measure out and drill holes for the pipe penetration. The hole must be 5 mm larger than the pipe itself, follow the wall box manufacturer's





19) Then slide the second panel into the profile trim. If the corner is in a wet zone, make sure that the sealant seeps out along the entire joint.



15) When installing a wall box for a pipe-in-pipe system, check the wall box manufacturer's installation instructions.









Outer corner

16) Make sure that the base profile trim is fitted as illustrated.



20) When the room is finished, the gap between the panel and the base profile trim must be sealed with Wetwall SEAL. Place masking tape 2–3 mm up on the panel so that the sealant runs from the base profile trim to the outer edge of the panel. Also make sure that there is sufficient sealant where the base profile trim comes into contact with the upper edge of the flooring. Remove excess sealant.




17) Adjust the panels to the external corner. Press the external corner profile onto the end panel from the first wall. If the corner is in a wet zone, Smartpanel Wetwall SEAL must be applied to both sides of the profile trim before it is placed on the panel. It is important that the sealant seeps out along the entire length of the joint, between profile trim and panel.



Joint sealing of base profile trim


21) After a few days, the sealing of the base profile trim must be checked and resealed if necessary.

All joints must be checked regularly. Carry out regular visual inspections and replace damaged or discoloured sealant with new sealant if necessary.




18) Screw the profile trim to the wall, and then fasten with the screws provided with the system. Use the predrilled holes in the profile trim.

22) "Våtromsnormen" (the Norwegian trade standard for wet rooms):



Wetwall accessories:



- 13 screws per panel

· 1 tube of sealant per 5 panels





For installationvideo and animation - visit smartpanel.no/en eller YouTube.



For approved installation, TEK 17 Section 13–15 "Wet rooms and rooms with water installations" must be observed.

Where Wetwall is to act as a vapour barrier, the panels must be installed as in wet zones.

