

# Twofold Warning System Zyklop 220 LED L8H

- Energy-efficient design with only one LED
- Automatic day/night adaptation, switchable to solar switch
- 5 m connecting cable with battery clips per system
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m
- Approved according to EMC directive
- Bracket for tubes up to 82 mm (optional)



**Eff. light intensity**  
1575 cd



**Light colour**  
amber



**Weight**  
1.2 kg/set



**Blink-/flash rate**  
60 fl./min.



**Light source**  
1 LED



**Av. power consu2**  
12/24 V



**Operating voltage**  
12/24 V



**Dimensions**  
Ø 220 mm / height: 74 mm



**Av. power consumpt. day**  
0.28 A

## Twofold Warning System Zyklop 220 LED L8H

### Order number

Twofold Warning Light System Zyklop 220 LED L8H, 671/1 NiBus, 12/24 V, with 5 m connecting cable with battery clips on master lamp

122222-1

## Accessories and Spare parts

### Order number

Bracket for tubes up to 82 mm

365522-12

Box for rechargeable batteries 12 V up to 230 Ah, lockable

190230-2

## Operating time with a battery pack

With rechargeable battery 12 V, 180 Ah

800 hrs

With rechargeable battery 12 V, 100 Ah

440 hrs

With rechargeable battery 12 V, 230 Ah

1000 hrs



twof. Warning System Zyklop 220 LED L8H



Twofold Warning System with bracket



Box for rechargeable batteries



Further information  
NIS-00245

Verification number:  
V3-24-2013

