



DECLARATION of PERFORMANCE

According to Commission Delegated Regulation (EU) No 574/201
Amending Annex III to Regulation (EU) No 305/2011

No 2020-08-5A

1. Unique identification code of the product-type: **Woven Polyester Geotextile GTX-W TeleVev 150/150**
2. Intended uses: Reinforcement, filtration & separation of roads (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of railways (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of earthworks, foundations (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of erosion control works (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of reservoirs and dams (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of canals (R, F, R+S, F+S, R+F+S)
3. Manufacturer: **SIA “Tele Textile Latvia”**
Ziemeļu Street 19, Liepāja LV-3405, Latvia Phone: +371 634 47302
4. System of AVCP: **2+**
5. Harmonized standards: **EN 13249:2016; EN 13250:2016; EN 13251:2016;
EN 13253:2016; EN 13254:2016; EN 13255:2016**
- Notified Body: **1488, INSTYTUT TECHNIKI BUDOWLANEJ**
ul. FILTROWA 1, 00-611 WARSZAWA
tel.: (0 22) 57 96 167,168, (0 22) 825 52 29, fax: (0 22) 57 96 295
e-mail: certyfikacja@itb.pl, www.itb.pl
6. Declared performances:

| Properties | Standard | Unit | Value | Tolerance |
|----------------------------------|--------------|--|-------|-----------|
| Tensile Strength (MD) | EN ISO 10319 | kN/m | 170 | - 20 |
| Tensile Strength (CMD) | EN ISO 10319 | kN/m | 170 | - 20 |
| Elongation at max. load (MD) | EN ISO 10319 | % | 10 | ± 2 |
| Elongation at max. load (CMD) | EN ISO 10319 | % | 10 | ± 2 |
| Static puncture resistance (CBR) | EN ISO 12236 | kN | 19 | -3 |
| Characteristic opening size O90 | EN ISO 12956 | µm | 80 | ± 35 |
| Dynamic perforation (cone drop) | EN ISO 13433 | mm | 12 | + 7 |
| Velocity index (VH50) | EN ISO 11058 | ms ⁻¹ | 0,005 | - 0,003 |
| Durability | Annex B | Reinforcement or other application where long-term strength is required: to be covered within 1 day after installation. Other application where long-term strength is not required: to be covered within 2 weeks after installation. Predicted to be durable for a minimum of 25 years in natural soils with 4 < pH < 9 and soils temperatures < 25° C | | |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

Member of the Board: Mr. Edijs Egļiņš:

(signature)

Quality Manager: Mrs. Natalja Fjodorova

(signature)

SIA Tele Textile Latvia
Reg. Nr. 42103068550
Ziemeļu iela 19, Liepāja
Latvija, LV-3405



The document was issued at Liepāja on November 2020