

**DECLARATION of PERFORMANCE**

According to Commission Delegated Regulation (EU) No 574/2011  
Amending Annex III to Regulation (EU) No 305/2011

**No 2019-08-10A**

1. Unique identification code of the product-type: **Woven Polyester Geotextile GTX-W TeleVev 200/50**
2. Intended uses: Reinforcement, filtration & separation of roads (R, F, R+S, F+S, R+F+S)  
Reinforcement, filtration & separation of railways (R, F, R+S, F+S, R+F+S)  
Reinforcement, filtration & separation of earthworks, foundations (R, F, R+S, F+S, R+F+S)  
Reinforcement, filtration & separation of erosion control works (R, F, R+S, F+S, R+F+S)  
Reinforcement, filtration & separation of reservoirs and dams (R, F, R+S, F+S, R+F+S)  
Reinforcement, filtration & separation of canals (R, F, R+S, F+S, R+F+S)
3. Manufacturer: **SIA “Tele Textile Latvia”**  
Ziemeļu Street 19, Liepāja LV-3405, Latvia Phone: +371 634 47302
4. System of AVCP: **2+**
5. Harmonized standards: **EN 13249:2016; EN 13250:2016; EN 13251:2016;  
EN 13253:2016; EN 13254:2016; EN 13255:2016**
- Notified Body: **1488, INSTYTUT TECHNIKI BUDOWLANEJ**  
ul. FILTROWA 1, 00-611 WARSZAWA  
tel.: (0 22) 57 96 167,168, (0 22) 825 52 29, fax: (0 22) 57 96 295  
e-mail: [certyfikacja@itb.pl](mailto:certyfikacja@itb.pl), [www.itb.pl](http://www.itb.pl)
6. Declared performances:

Properties	Standard	Unit	Value	Tolerance
Tensile Strength (MD)	EN ISO 10319	kN/m	220	- 20
Tensile Strength (CMD)	EN ISO 10319	kN/m	70	- 20
Elongation at max. load (MD)	EN ISO 10319	%	10	± 2
Elongation at max. load (CMD)	EN ISO 10319	%	10	± 2
Static puncture resistance (CBR)	EN ISO 12236	kN	12	- 3
Characteristic opening size O90	EN ISO 12956	µm	100	± 35
Dynamic perforation (cone drop)	EN ISO 13433	mm	20	+ 7
Velocity index (VH50)	EN ISO 11058	ms <sup>-1</sup>	0,006	- 0,003
Durability	Annex B	Reinforcement or other application where long-term strength is required: to be covered within 1 day after installation. Other application where long-term strength is not required: to be covered within 2 weeks after installation. Predicted to be durable for a minimum of 50 years in natural soils with 4 < pH < 9 and soils temperatures < 25° C		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

Member of the Board: Mr. Edijs Egļiņš:

(signature)

Quality Manager: Mrs. Natalja Fjodorova

(signature)

**SIA Tele Textile Latvia**  
Reg. Nr. 42103068550  
Ziemeļu iela 19, Liepāja,  
Latvija, LV-3405



The document was issued at Liepāja on November 2020