

Løsflens presset Rustfrie EN 1.4307/304L. ISO

**NRF nr.**

1800403 t.o.m 1800417

PRODUKTDATA

Lev.varenr.	FST03860
Produkttype	Løsflenser presset DIN 2642
Materiale	Rustfritt/Syrefast
Dim.	DN15/21,3 mm

PRODUKTBESKRIVELSE

Rustfritt EN 1.4307. Boret etter DIN 2642. Sertifikat EN 10204/3.1. Prisene er inkl. legeringstillegg.

NRF nr.	Dim.	Boltesirkeldia.mm	Hull	Trykk	Kg pr stk	Enh.	RG	LS
1800403	DN15/21,3 mm	65 mm	4	PN 16	0,67 kg	STK	VM	*
1800404	DN20/26,9 mm	75 mm	4	PN 16	0,81 kg	STK	VM	*
1800405	DN25/33,7 mm	85 mm	4	PN 16	1,11 kg	STK	VM	*
1800406	DN32/42,4 mm	100 mm	4	PN 16	1,5 kg	STK	VM	*
1800407	DN40/48,3 mm	110 mm	4	PN 16	1,86 kg	STK	VM	*
1800408	DN50/60,3 mm	125 mm	4	PN 16	2,2 kg	STK	VM	*
1800409	DN65/76,1 mm	145 mm	4	PN 16	2,62 kg	STK	VM	*
1800411	DN80/88,9 mm	160 mm	8	PN 16	3,32 kg	STK	VM	*
1800412	DN100/114,3 mm	180 mm	8	PN 16	3,67 kg	STK	VM	*
1800413	DN125/139,7 mm	210 mm	8	PN 16	4,54 kg	STK	VM	*
1800414	DN150/168,3 mm	240 mm	8	PN 16	5,60 kg	STK	VM	*

NRF nr.	Dim.	Boltesirkeldia.mm	Hull	Trykk	Kg pr stk	Enh.	RG	LS
1800415	DN200/219,1 mm	295 mm	8	PN 10	3,62 kg	STK	VM	*
1800416	DN250/273,0 mm	350 mm	12	PN 10	10,3 kg	STK	VM	*
1800417	DN300/323,9 mm	400 mm	12	PN 10	14,0 kg	STK	VM	*