


BIS Reduktionsmuffe (M/F)

justering af gevindtilslutning

(K 55 35)



Funktioner og fordele

■ for at forstørre eller reducere gevindstørrelsen på rørbøjler, mm.

■ materiale: stål
■ elforzinket
■ brandtestet

Art.nr.	L	G1	G2	Lm1 (mm)	Lm2 (mm)	SW1 (mm)	Pakke1	Pakke2
647 3 008	19,0 mm	M6	M8	7,0	12,0	13	100	1.000
647 3 206	20,0 mm	M8	M6	8,0	12,0	13	100	2.000
647 3 210	19,5 mm	M8	M10	6,5	13,0	13	100	2.000
647 3 212	23,0 mm	M8	M12	8,0	15,0	17	50	-
647 3 221	30,0 mm	M8	1/2"	8,0	22,0	27	50	250
647 3 308	21,0 mm	M10	M8	8,0	13,0	13	100	2.000
647 3 312	25,0 mm	M10	M12	10,0	15,0	17	50	500
647 3 316	32,0 mm	M10	M16	10,0	22,0	24	50	-
647 3 321	31,0 mm	M10	1/2"	10,0	21,0	27	25	250
647 3 408	23,0 mm	M12	M8	10,0	13,0	13	50	1.000
647 3 410	23,0 mm	M12	M10	10,0	13,0	13	50	1.000
647 3 416	32,0 mm	M12	M16	10,0	22,0	24	50	-
647 3 510	32,0 mm	M16	M10	14,0	18,0	19	50	-
647 3 512	32,0 mm	M16	M12	14,0	18,0	19	50	-
647 3 521	15,0 mm	1/2"	M16	-	15,0	-	50	250

M10 og derover er brandtestet.

