



## VARIANTS

6120FZ | Washbasin faucet, 9/12 V, Bluetooth

6120FZ | WASHBASIN FAUCET, 9/12 V, BLUETOOTH

# Oras Electra

## EANCODE

6414150095825

## ACTIVEMARKETAREAS

**INT, DNK, EST, FIN, LVA, LTU,**

**NOR, POL, RUS, SWE, UKR**





# Oras Electra

More than 30 years of experience in electronic faucets truly shows in Oras Electra, our most widely used and versatile touchless faucet family. Oras introduced the touchless faucets in the public premises already in the 1990s, and in the 21st century, the electronic faucets have rapidly become more common also in the household use. With touchless faucets, water consumption can be reduced by half, while user-friendliness and hygiene rise to a whole new level.

## Features

### Additional features

Electrical connection 12 V via a separate power supply (e.g. Oras No. 199275/199550).

---

### Aerator

PCA® - constant flow rate regardless of pressure variations, Standard aerator

---

### Connection

Flexible inlet pipes

---

### Electronic parts

Autofocus infrared sensor, Solenoid valve

---

### Lever/Handle

Temperature control handle

---

### Mechanical parts

Non-return valve(s), Litter filter(s),  
Mixing valve for manual temperature control

---

### Special features

Software settings adjustable via App,  
Convertible for cold or premixed-water  
supply

---

Spout  
Fixed spout, Casted construction

---

Color  
Chrome

---

Temperature  
Temperature preset ?xable

---

## Software settings

After?ow period  
3 s (1-20 s)

---

Automatic ?ush  
off (off/1-120h)

---

Automatic ?ush period  
30 s (1-1800 s)

---

Max. ?ow period  
2 min (1 - 1800 s)

---

## Flow attributes

Flow-rate at 300 kPa (with ?ow controller)  
0.1 l/s

---

Pressure loss with ?ow (0.1 l/s)  
200 kPa

---

## Technical properties

Connection size  
G3/8

---

DN-size (nominal dimension)  
DN15

---

Hot water supply  
max. +70°C

---

Material

Brass

---

Projection

96 mm

---

Working pressure

50 - 1000 kPa

---

## Electronics

Electrical Connection

9/12 V

---

## Regulations

EMC Directive

2014/53/EU

---

Noise class

I (ISO 3822)

---

Protection class

IP 55

---

## Approvals

GDV Danmark

04/00229

---

STF

EUFI-RTH+00031-11