

# BIS RapidStrut® Fixing Rail (pg)

(H 04 10)

suspension and support



## Features and benefits

- universal rail system
- with continuous perforation
- distance between rail end and first hole is always equal
- a continuous graduated centimetre scale on one side
- inward formed flanges with serrated profile for extra grip
- pre-galvanized
- material: steel 1.0242
- Part No. 650 5 X85 (Strut 2.5 mm) material: steel 1.0332
- yield strength 240 N/mm<sup>2</sup>
- strut 41x41x2.5 and above tested for fire safety

Part No.	Model	L	B	H	s	S	RAL	BndS	BndL	App.
		(mm)	(mm)	(mm)	(mm)	(mm)				
6505224	Perforated	2 m	41	21	1.50	22	RAL <sup>1</sup>	20	200	m.
6505324	Perforated	3 m	41	21	1.50	22	RAL <sup>1</sup>	30	300	m.
6505624	Perforated	6 m	41	21	1.50	22	RAL <sup>1</sup>	60	600	m.
6505225	Perforated	2 m	41	21	2.50	22	RAL <sup>1</sup>	20	200	m.
6505325	Perforated	3 m	41	21	2.50	22	RAL <sup>1</sup>	30	300	m.
6505625	Perforated	6 m	41	21	2.50	22	RAL <sup>1</sup>	60	600	m.
6505244	Perforated	2 m	41	41	1.50	22	RAL <sup>1</sup>	20	100	m.
6505344	Perforated	3 m	41	41	1.50	22	RAL <sup>1</sup>	30	150	m.
6505644	Perforated	6 m	41	41	1.50	22	RAL <sup>1</sup>	60	300	m.
6505242	Perforated	2 m	41	41	2.00	22	RAL <sup>1</sup>	20	100	m.
6505342	Perforated	3 m	41	41	2.00	22	RAL <sup>1</sup>	30	150	m.
6505245	Perforated	2 m	41	41	2.50	22	RAL <sup>1</sup>	20	100	m.
6505345	Perforated	3 m	41	41	2.50	22	RAL <sup>1</sup>	30	150	m.
6505645	Perforated	6 m	41	41	2.50	22	RAL <sup>1</sup>	60	300	m.
6505365	Perforated	3 m	41	62	2.50	22	-	30	90	m.
6505665	Perforated	6 m	41	62	2.50	22	-	60	180	m.
6505385	Perforated	3 m	41	82	2.50	22	-	180	-	m.
6505685	Perforated	6 m	41	82	2.50	22	-	60	180	m.
6505620	Not perforated	6 m	41	21	2.50	22	-	60	600	m.
6505640	Not perforated	6 m	41	41	2.50	22	-	60	300	m.

RAL<sup>1</sup> = tested, certified and monitored by a third party according to RAL-GZ 655/C.


Strut 41x41x2.5 and above tested for fire safety.

For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.

For more information about the max. allowed load ( $F_{0,2}$ ) please refer to the loading tables or our online datasheet 'Technical Details BIS RapidStrut®'.



RAL-GZ 655/C  
Cert.Nr. 2012-04



### Complementary

BIS RapidStrut® Hammerfix G2 (BUP1000)  
BIS RapidStrut® Slide Nut G2 (BUP1000)

### Alternative

BIS RapidStrut® Fixing Rail DS 5  
(BUP1000)