



Rillade produkter | Rörkopplingar och rördelar

Böjar 22,5°



Godkännanden



Nominell storlek		Rör YD	Artikelnr.		Godkännanden				Vikt ca.
DN	Tum	mm (tum)	Röd färg	Galvaniserad	VdS	LPCB	FM	UL	kg (pund)
32	1-1/4	42,4 (1,66)	919700	919759	-	-	F	F	0,32 (0,72)
40	1-1/2	48,3 (1,90)	919704	919760	-	-	F	F	0,37 (0,82)
50	2	60,3 (2,38)	919707	919761	-	-	F	F	0,52 (1,14)
65	3 YD	76,1 (3,00)	919712	919763	C	E	F	F	0,87 (1,92)
80	3	88,9 (3,50)	919715	919764	C	E	F	F	1,07 (2,37)
100	4	114,3 (4,50)	919718	919765	C	E	F	D	1,89 (4,16)
125	5-1/2 YD	139,7 (5,50)	919722	919766	C	E	F	D	2,72 (6,00)
150	6-1/2 YD	165,1 (6,50)	919727	919767	-	E	F	D	3,63 (7,99)
	6	168,3 (6,63)	919730	919768	C	-	F	D	4,53 (9,99)
200	8	219,1 (8,63)	919731	919769	C	E	D	D	6,83 (15,10)

YD = ytterdiameter

Arbetstryck: **A** = max. 12,1 bar (175 psi) / **B** = max. 15,5 bar (225 psi) / **C** = max. 16 bar (232 psi) / **D** = max. 20,7 bar (300 psi) /

E = max. 25 bar (363 psi) / **F** = max. 34,5 bar (500 psi) / - = inga godkännanden

Tekniska data

Typ..... 110

Material..... segjärn


Yta:

- Röd färg flytande färg likande RAL 3000

- Galvaniserad varmgalvaniserad

Måttitning

Mått i mm (tum)



Tillämpning

Vattenbaserade brandbekämpningssystem

Installation

Se "Rillade produkter: Installationsanvisningar"

Underhåll

Visuell kontroll

DN	Tum	L (mm/tum)
32 / 42,4	1-1/4	45 (1,77)
40 / 48,3	1-1/2	
50 / 60,3	2	48 (1,89)
65 / 76,1	3 YD	51 (2,00)
80 / 88,9	3	57 (2,24)

DN	Tum	L (mm/tum)
100 / 114,3	4	73 (2,87)
125 / 139,7	5-1/2 YD	
150 / 165,1	6-1/2 YD	79 (3,11)
150 / 168,3	6	
200 / 219,1	8	98 (3,86)