



DECLARATION of PERFORMANCE

According to Commission Delegated Regulation (EU) No 574/201
Amending Annex III to Regulation (EU) No 305/2011

No 2020-08-8A

1. Unique identification code of the product-type: **Woven Polyester Geotextile GTX-W TeleVev 300/50**
2. Intended uses: Reinforcement, filtration & separation of roads (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of railways (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of earthworks, foundations (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of erosion control works (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of reservoirs and dams (R, F, R+S, F+S, R+F+S)
Reinforcement, filtration & separation of canals (R, F, R+S, F+S, R+F+S)
3. Manufacturer: **SIA “Tele Textile Latvia”**
Ziemeļu Street 19, Liepāja LV-3405, Latvia Phone: +371 634 47302
4. System of AVCP: **2+**
5. Harmonized standards: **EN 13249:2016; EN 13250:2016; EN 13251:2016;
EN 13253:2016; EN 13254:2016; EN 13255:2016**
- Notified Body: **1488, INSTYTUT TECHNIKI BUDOWLANEJ**
ul. FILTROWA 1, 00-611 WARSZAWA
tel.: (0 22) 57 96 167,168, (0 22) 825 52 29, fax: (0 22) 57 96 295
e-mail: certyfikacja@itb.pl, www.itb.pl
6. Declared performances:

Properties	Standard	Unit	Value	Tolerance
Tensile Strength (MD)	EN ISO 10319	kN/m	350	-50
Tensile Strength (CMD)	EN ISO 10319	kN/m	70	-20
Elongation at max. load (MD)	EN ISO 10319	%	10	± 2
Elongation at max. load (CMD)	EN ISO 10319	%	10	± 2
Static puncture resistance (CBR)	EN ISO 12236	kN	13	-3
Characteristic opening size O ₉₀	EN ISO 12956	µm	90	± 35
Dynamic perforation (cone drop)	EN ISO 13433	mm	12	+7
Velocity index (V _{H50})	EN ISO 11058	ms ⁻¹	0,005	-0,003
Durability	Annex B	Reinforcement or other application where long-term strength is required: to be covered within 1 day after installation. Other application where long-term strength is not required: to be covered within 2 weeks after installation. Predicted to be durable for a minimum of 50 years in natural soils with 4 < pH < 9 and soils temperatures < 25° C		


The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

Member of the Board: Mr. Edijs Egļiņš:

(signature)

SIA Tele Textile Latvia
Reg. Nr. 42103068550
Ziemeļu iela 19, Liepāja,
Latvija, LV-3405



Quality Manager: Mrs. Natalja Fjodorova

(signature)

The document was issued at Liepāja on November 2020